



2500 Material Hoist / Transport Platform

Protecting the Payload

Ideal for roofing, masonry
and restoration/renovation

BRAND SAFWAY®

At Work For You®

› Transport fragile materials easily and safely.

Low-anchor forces allow installation to most structures or scaffolds, while small footprint fits into confined spaces (10' x 10').



Dual speed motor for customizing lift can run off three-phase or single-phase power. Soft Start and Stop VFD technology keeps materials safe.

2500 Material Hoist / Transport Platform Specifications

- › Platform dimensions: 4'3" (W) x 7'2" (L)
- › Loading height: 16"
- › Unit weight: 1,918 lbs.
- › Maximum payload: 2,500 lbs.
- › Maximum number of people:
Six – transport platform only
- › Travel speed: 40 fpm transport platform;
80 fpm material hoist
- › Maximum height: 400'
- › Maximum tie spacing: 20'
- › Drive system: Rack and pinion
- › Motors: Two each – MGM 6 hp
- › Power requirements: 208 volt, 3 phase, 65 amp;
230 volt, single phase, 65 amp
- › Safety devices: Gravity-activated manual
centrifugal brake – 98 fpm tripping speed

* Tie configuration may vary from that shown.

**YOUR LOCAL
EXPERT** › COMMERCIAL
CONSTRUCTION
ACCESS SOLUTIONS

+Safety
First and Foremost

+Expertise
Industry-Leading Depth/Range

+Solutions
The Broadest Portfolio

+Productivity
Increased at Every Level

+Local
Management and Labor

Visit [BrandSafway.com](https://www.brand-safway.com)
to connect with Your Local Expert

BRAND SAFWAY